


SHREE CEMENT LIMITED

(UNIT-SHREE RAIPUR CEMENT PLANT)









SRCP /BB//2018-18/63

Date: 03.09.18

To, The Member Secretary, Chhattisgarh Environment Conservation Board, Paryavas Bhavan, North Block, Sector-19 Naya Raipur (C.G)

Sub: - Submission of Environment Statement of Shree Lime Stone mine for the year 2017-18 by Shree Raipur Cement Plant (A unit of Shree Cement Ltd.) mine located at Village Semaradih and Bharuwadih in Baloda Bazar - Bhatapara District (Chhattisgarh).

Ref: 1. Consent to Operate(Water)letter No.- 5023/TS/CECB/2017, dated 13/12/2017. 2. Consent to Operate (Air) letter No.- 5025/TS/CECB/2017, dated 13/12/2017.

Dear Sir.

Kindly referred to above subject matter and reference letter. In this regards, we are submitting herewith the Environmental Statement for the year 2017-18 of Shree Lime Stone Mine located at Village Semaradih and Bharuwadih in Baloda Bazar - Bhatapara District (Chhattisgarh).

Hope you will find this in Order

Thanking you,

Yours faithfully, For Shree Raipur Cement Plant (A unit of Shree Cement Ltd.)

R K Wijay AVP (Operations)

Enclosed: - As above.





CC to:- Regional Officer, Chhattisgarh Environment Conservation Board, Commercial Complex, Chhattisgarh Housing Board Colony Kabir Nagar, Raipur (C.G.) - 492099

ENVIRONMENTAL STATEMENT

FORM - V

Shree Raipur Cement Plant

(A Unit of Shree Cement Itd)

(Shree Lime Stone Mine)

Period from: April 2017 to March 2018

PART - A

1.	Name and address of the Owner / Occupier of the Industry operation or process	Shree Lime Stone Mine M/s Shree Cement Itd Village – Bharuadih - Semradih, Tahsil – Balodabazar, Distt – Baloda Bazar -Bhatapara Chhattisgarh – 493332
2.	Industry Category Primary (S.T.C. Code) Secondary (S.T.C. Code)	Red Category
3.	Production Capacity	8.6 Million TPA Limestone
4.	Year of Establishment	2015
5.	Date of the last Environmental Statement Submitted	06/09/2017

WATER AND RAW MATERIAL CONSUMPTION

(I) WATER CONSUMPTION:

Process : N.A.

Cooling and dust : 132.6 KLD

Suppression

Domestic : 2.56 KLD

As

Name of	Process Water Consumption (KL/MT of	per Unit of Product Output Lime stone)
Product	During Previous Financial Year (2016-17)	During Current Financial Year
		(2017-18)
Limestone mine	0.011	0.0106

(II) RAW MATERIAL CONSUMPTION:

Name of Raw Materials	Name of Products	ucts Consumption of raw material poutput	
		During Previous Financial Year (2016-17)	During Current Financial Year (2017-18)
Lime Stone		2993943 MT	4112837 MT

(III) POWER CONSUMPTION (KWH/T OF LIMESTONE):

During Previous Financial Year (2016-17)	During Current Financial Year (2017-18)
1.54	1.63

(IV) TOTAL LIMESTONE PRODUCTION (MT):

During Previous Financial Year	During Current Financial Year
(2016-17)	(2017-18)
2993943	4112837



PART - C

	Quantity of Pollutants Discharged (Mass/Day)	Concentration of Pollutants in Discharge (Mass/Value)	Percentage of variation from prescribed standard with reasons
(a)	Water	Waste water generated treated with septic tank	d from office toilets is & soak pit.
		Waste water generated being reutilized for was oil & grease contaminant	from washing ramp is shing after separating the
(b)	Air	Please refer Annexure –	

PART - D

HAZARDOUS WASTE

((As specified under Hazardous & other wastes (Management and Transboundary Movement) Rule, 2016)

Hazardous Waste	Movement) Rule, 2016) Total Quantity (Ltrs.)		
a)From Process	Financial Year (2016-17)	During Current Financial Year (2017-18))	
(Cement manufacturing is based on "Dry Process" No Hazardous waste is generated from the process except used oil which is drained from Machinery / Equipments)	Cement Plant & Mines).	Nil	
b) From Pollution Control Facilities	N.A.	N.A.	

A3

<u>PART – E</u> SOLID WASTE

		Total Quantity (MT)	
(-)		During Previous Financial Year (2016-17)	During Current Financial Year (2017-18)
(a)	From Process	Not Ap	plicable
(b)	From Pollution Control Facility	Not Applicable	
(c)	Quantity rejected or re- utilized within the unit	Not Applicable	
	2. Solid	Not Applicable	
	3. Disposed (During mining of limestone disposed of overburden)	Not Ap	рпсавте
	a. Top soil for reclamation (MT)	359600	358573
	a. Over burden (MT)	779376	1883902
	b. Total Qty (MT)	1138976	2242475

Note:- Overburden is being dumped along with mine lease area A Plantation is also being done on the overburden.

PART - F

Please specify the characterization (in terms of composition and quantum) of hazardous as well as solid wastes and indicate disposal practice adopted for both the categories of wastes:

Battery Wastes:

As specified under Batteries (Management and Handling) Amendment Rules, 2010, we have purchased following new batteries of different categories.

Number of new batteries of different categories purchased from the manufacturer / importer / dealer or any other agency.	During Current Financial Year April,2017 to March,2018	
Category:	No of Batteries	Approximate Weight
(i) Automotive		(In Tons)
a) Four wheeler		
	44	1.86

A3

b) Two wheeler	0 1	0
(ii) Industrial		U
a) UPS (Vrla Type)	439	4.19
b) Motive Power	0	0
c) Stand -by	0	0
(iii) Others	Nil	Nil
Total	483 Nos.	6.051 MT

Number of used batteries of different categories sent to manufacturer/dealer/importer/registered recycler/or any other agency	During Current Financial Yea April,2017 to March,2018	
Category:	No of Batteries	Approximate Weight (In Tons)
(i) Automotive		(III TOIIS)
a) Four wheeler	160	4.34
b) Two wheeler	Nil	Nil
(ii) Industrial		INII
a) UPS	104	1.0
b) Motive Power	Nil	Nil
c) Stand –by	Nil	Nil
(iii) Others	Nil	Nil
Ised battery screen will be sent to eath in a	264	5.34

Used battery scrap will be sent to authorized recycler

Hazardous Wastes

No Hazardous waste is generated from the process except used oil which is drained from HEMM / Equipment's. The used oil & Acid Lead will be sold to CPCB authorized recyclers.

E-WASTE

	Total Quantity (MT)	
	During Previous Financial (2016-17)	During Current Financial Year (2017-18)
April, 2017 to March,2018	Nil	Nil

Note- E-Waste Will be sold to approved E- Waste Recycler



PART - G

IMPACT OF THE POLLUTION CONTROL MEASURES ON CONSERVATION OF NATURAL RESOURCES AND CONSEQUENTLY ON THE COST OF PRODUCTION

- Low grade limestone is used with high grade lime stone for conservation of Mineral as well as increase of reserves.
- 2. Bag filter has been installed at crusher I & II
- 3. Wet drilling is being done by Wet drilling Machine.
- 4. Blasting is being done by as per working permission of DGMS under regulation 106 of MMR1961.
- 5. Controlled Blasting is being done by latest technology by using shock tube detonators of down the hole delay (in millisecond) as well as trunk line delay (in millisecond) to control noise level, vibration and fly rock. Which is regularly monitored by latest series of Seismograph Micro mate.
- 6. Two Water Tanker capacity 20 KL & 18 KL each engaged for Water spray arrangement is provided on haul road.
- 7. Water spraying arrangement / Dust suppression system has been provided at the unloading point of limestone crusher hopper & Discharge end of belt conveyor
- 8. Fugitive dust at loading point is controlled by pressurized water mist spray arrangement of water tanker.
- 9. Installed 1.5 km pipe conveyor system in Crusher-I for transportation of mineral from mines to plant so there are no fugitive emissions as there is no transfer point.
- 10. Installed 3.3 KM length closed conveyor from crusher-II to plant for transportation of mineral. Bag filters has installed at transfer point to reduce fugitive emission.
- 11. Constructed permanent CC road having length of 1.8 Km from mine crusher-I to plant for compliance of CECB so that there is no dust formation along permanent road.
- 12. All HEMM being provided with AC operator's cabin to overcome noise & dust pollution as well as to improve operator efficiency.
- 13. All HEMM machines are Komatsu Japan having certification of American standards EPA (Env. Protection agency) Tier 2& Tier-3 as producing low NOX & SOX within permissible limit.



ADDITIONAL MEASURES / INVESTMENTS PROPOSAL FOR ENVIRONMENT PROTECTION INCLUDING ABATEMENT OF POLLUTION

- Garland drains all around the waste dump yard have been made for stability of dumps.
- 2. Over burden dumps has been stabilized by proper benching as per approved mining plan. It is also stabilized by growing with suitable native species.
- 3. Waste is dumped in non-mineralized zone/area as well as per approved mining plan.
- 4. At present there is no Inter burden generated.
- 5. 139186 plants have been planted to improve greenery.
- 6. Under Hariyar Chhattisgarh project, we have planted 15000 trees near School of Bharuwadih, Semradih, Khapradih, Chandi, Karahi & Parkidih villages with about 10 KM of both side of road plantation from Bharuwadih to chandi village and this year; we have also planted about 15000 trees at Bhatapara.
- 7. stack monitoring at crusher no.1 & 2 being carried out for compliance of CECB on regular basis.(report enclosed)
- 8. Developed 2 nos of water harvesting pond having capacity of 2.5 lacs KL at outside of pit area and 3 KL at lower benches of our active pit for conservation as well to improve water table of area.

ANY OTHER PARTICULATES FOR IMPROVING THE QUALITY OF ENVIRONMENT.

- 1. All the operators having provided PPE & Earplug & Ear muff to meet out noise pollution and regular noise survey being done at all HEMM.
- 2. Regular dust survey being carried out as per DGMS Norms
- 3. Two Rock breaker machines being used for breaking of oversize boulders instead of secondary blasting which eliminated vibration, noise, fly rocks & reducing greenhouse gases which have caused due to secondary blasting.
- 4. Wet drilling system with drilling being used while drilling so that dust is suppressed immediately.

- 5. Blasting is being done by using slurry explosive and ANFO, having low velocity of detonation therefore it will air pollution as well as ground vibration. Non electric blasting system is used to reduce ground vibration.
- Construction of grease and oil chambers at washing ramp to avoid pollution.
 Separated oil and grease from water. It will also help to recirculate water for dust suppression.
- 7. Isnstalled 4 numbers of online Ambient Air Quality Monitoring Stations.
- 8. Maintenance department is doing regular checking and scheduled maintenance of all the pollution control devices.

Ture to I	above, we are enclosing herewith following:- : Stack Emission monitoring report.
Annexure-2	: Ambient Air Quality Monitoring Station Report.

Annexure-I

Shree Lime Stone Mine
Stack Emission Report (PM All values in mg/Nm3)

S. No.	Month	Mines Crusher- I	Mines Crusher- II
1	Apr-17	19.7	NM
2	May-17	14.2	NM
3	Jun-17	17.9	NM
4	Jul-17	25.3	NM
5	Aug-17	20.9	NM
6	Sep-17	15.5	NM
7	Oct-17	17.4	NM
8	Nov-17	16.2	NM
9	Dec-17	20.2	NM
10	Jan-18	21.3	14.0
11	Feb-18	15.6	21.2
12	Mar-18	10.9	12.0



Shree Raipur Cement Plant (A Unit of Shree Cement Itd) AMBIENT AIR QUALITY MONITORING STATION

	Control of the Contro			AMBI	ENI AIR OU	AMBIEN AIR QUALITY MONITORING STATION DATA	ORING STAT	ATAC NOT						
Location	Parameters	Unit	Apr-17	May-17	Jun-17	Jul-17	A110-17	Son 17	11	Mar. 47	-:			
A A C PAGE 1 (AA)	PM 10		28.56	21	14.03	13.77	17 77	77.70	OCC-TV	NOV-1/	Dec-17	Jan-18	Feb-18	Mar-18
AACINIS I (MINES	DAM 2 S		1.00	17	14:00	17.77	11.11	26.49	37.3	32.0	34.3	31.2	27.6	40.2
boundary towards	200		7.88	10.31	9.43	6.84	10	15.22	19.5	14.9	16.6	12.4	14.2	19.2
village Bharuwadih)	37.57		4.06	3.89	3.88	4.11	4.7	14.01	7.0	5.4	5.8	6.1	5.6	5.2
	NOZ		2.77	1.99	3.34	2.05	0.45	2.2	4.1	5.3	3.9	4.1	47	2.0
AAQMS 2 (Mines	PM 10		58.98	36.31	25.99	19.89	22.05	29.28	35.2	767	22.0	33.7	36.7	0.0
houndary towards	PM 2.5		47.17	9.41	9.93	8.67	12.3	13 03	100		2.72	32/	200.7	21.7
Spinor dimension	502		7 03	7.05	12	20:02	77.77	13.03	10.8	14.6	11.7	13.6	16.5	25.8
VIIIagesemradih)	2014		66.7	50.7	7.7	1.26	7.42	10.44	7.3	6.9	6.7	4.9	3.3	38
	NOZ	Cm/mi	12.41	10.63	0.2	0.38	0.81	7.81	4.4	7.1	5.0	3.5	3.1	200
ANONA STORY	PM 10	HE/III)	47.1	22.37	23.76	167	10 47	25 72	000	-	25	6:3	3.1	7.4
ANGELINES OF INSTITUTE	DAM 2 S		27.70		200	1.04	10.4/	23.73	30.9	43.4	35.2	21.1	34.8	61.6
Boundary towards	C.7 141		17.39	9.3	7.8	7.38	11.18	10.95	18.7	24.0	17.9	10.6	175	32.7
South Diection)	502		20.16	14.02	4.1	3.83	3.69	3.4	3.3	4.4	a c	2.22	200	33.2
	NO2		8:38	8.36	8.37	8.37	517	1 63	7 3		000	2.7	0.0	0.1
	DAM 10					10:00	7:17	4.03	5.4	6.9	2.5	0.9	8.0	8.8
AAQMS 4 (Plant	OT IAI TO		67.54	24.26	19.57	19.89	18.85	30.62	38.6	38.0	33.2	28.9	38.2	48.1
Boundary towards	PM 2.5		39.43	11.63	8.01	7.33	9.86	14.89	19.3	15.0	14.7	0 1	300	10:1
	502		697	6.41	6 30	6.4		200	5.5	13.3	14./	11.8	15.3	22.0
(mpn.dp 80	NO	_	000	1	00.0	4.0	0.11	p.74	2.0	3.5	4.0	3.3	3.3	4.9
	NOZ		3.38	1.38	1.85	2.85	5.47	9.15	9.3	8.0	5.7	1.3	5.1	73
														2

